



### TOOLS AVAILABLE

The Invicta can be equipped with all tools compatible with the following tool holders:

- Multifunctional Tool Holder
- Versa-Tool Holder
- Fixed Tool Holder



MTH



FTH



VTH




### TECHNICAL DATA

Invicta Models	V0806	V0812	V1015	<b>NEW</b> V1612
Cutting Size	812 x 610 mm (32" x 24")	812 x 1219 mm (32" x 48")	1016 x 1524 mm (40" x 60")	1550 x 1220 (61" x 48")
Width	1450 mm (57")	1390 mm (54.7")	1590 mm (62.6")	2110 mm (83")
Depth	1390 mm (54.7")	1920 mm (75.5")	2080 mm (81.9")	1920 mm (75.6")
Height	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")	1250 mm (49.2")
Weight	206 kg (454.1 lbs)	228 kg (502.65 lbs)	265 kg (584.2 lbs)	329 kg (725 lbs)
Max Cutting Speed	Up to 400 mm/s (16"/sec)	Up to 400 mm/s (16"/sec)	Up to 400 mm/s (16"/sec)	Up to 910 mm/s (26.3"/sec)
Acceleration	Up to 0.5 m/sec <sup>2</sup> (19.7"/sec <sup>2</sup> )	Up to 0.5 m/sec <sup>2</sup> (19.7"/sec <sup>2</sup> )	Up to 0.5 m/sec <sup>2</sup> (19.7"/sec <sup>2</sup> )	Up to 2 m/sec <sup>2</sup> (78.7"/sec <sup>2</sup> )
Power Requirements	Single Phase - 230V 50Hz 9.6A - 2,2 KVA Single Phase - 208/230V 60Hz 12A - 2,5 KVA			
Air Requirements	6 bar (3,5 CFM) 8 bar (5,3 CFM) with Oscillating Tool			
File Format	SVG, .PLT, .DXF, .CF2, .HPGL, .XML, .PDF			
Tool Change	Manual			
Tools Available	90°, 45°, 40°, Embossing, Creasing, Drawing, Oscillating Tool and Kiss Cut tool			
Tool Holders	1 + 1F			
Connectivity	Ethernet or USB			
Data Buffer	External PC*			
Media Holding System	Vacuum Bed and Pneumatic Clamping System			
Fixed Tool	Pen (Optional)			
Cutting Capacity	0.1 > 5 mm (0.20") with Tangential Cutting Tool 0.1 < 20 mm (0.79") with Oscillating Tool			
Repeatability	≤0.1 mm			
Supported OS	Windows 7, 10, 11			
CropMarks Rec.	Camera (Included) + Software (Optional)			



Magnet sheet



Folding carton

\*air compressor and PC not included